

Description

Fastener Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097B418
Minimum Qty (MOQ):	335 EA
NSN:	5320-01-257-3285
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1097B4-18 Specifications

Fastener Length:	1.125 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.006 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.174 Inches Minimum And 0.196 Inches Maximum
Head Minor Diameter:	0.134 Inches Minimum And 0.144 Inches Maximum
Countersink Height:	0.029 Inches Nominal
Shear Strength:	24000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097B4-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.