

**Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097B49
Minimum Qty (MOQ):	505 EA
NSN:	5320-00-728-1495
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N NAS1097B4-9 Specifications

<b>Fastener Length:</b>	0.562 Inches Nominal
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.003 Inches Nominal
<b>Shank Diameter:</b>	0.125 Inches Nominal
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.174 Inches Minimum And 0.196 Inches Maximum
<b>Head Minor Diameter:</b>	0.134 Inches Minimum And 0.144 Inches Maximum
<b>Countersink Height:</b>	0.029 Inches Nominal
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 5056 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Specification/standard Data:</b>	80205-nas1097 Professional/Industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097B4-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.