

Description

Fastener Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1097B55 |
| Minimum Qty (MOQ): | 505 EA |
| NSN: | 5320-00-959-7458 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N NAS1097B5-5 Specifications

| | |
|---|--|
| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.003 Inches Minimum And 0.005 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.158 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.240 Inches Minimum And 0.247 Inches Maximum |
| Head Minor Diameter: | 0.185 Inches Minimum And 0.195 Inches Maximum |
| Countersink Height: | 0.037 Inches Nominal |
| Grip Length: | 0.078 Inches Nominal |
| Shear Strength: | 24000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Material: | Aluminum Alloy 5056 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Specification/standard Data: | 80205-nas1097 Professional/industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097B5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.