



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS1097D5-10**

## Description

length: 5/8" diameter: 5/32", solid rivet, flush shear head, 2017-t4 aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1097D510
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-210-8402
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1097D5-10 Specifications

<b>Fastener Length:</b>	0.615 Inches Minimum And 0.625 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.004 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.243 Inches Minimum And 0.248 Inches Maximum
<b>Head Minor Diameter:</b>	0.190 Inches Minimum And 0.200 Inches Maximum
<b>Countersink Height:</b>	0.039 Inches Maximum
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Special Features:</b>	Color Natural
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Mil-r-5674 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097D5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.