

Description

length: 5/8" diameter: 5/32", solid rivet, flush shear head, 2017-t4 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097D510
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-210-8402
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N NAS1097D5-10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.625 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.004 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.243 Inches Minimum And 0.248 Inches Maximum
Head Minor Diameter:	0.190 Inches Minimum And 0.200 Inches Maximum
Countersink Height:	0.039 Inches Maximum
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Special Features:	Color Natural
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Mil-r-5674 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097D5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.