

**Description**

length: 11/16" diameter: 5/32", solid rivet - 100°, flush shear head - 2017-t4 aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1097D511
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-257-0752
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N NAS1097D5-11 Specifications

<b>Fastener Length:</b>	0.6775 Inches Minimum And 0.6975 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.003 Inches Minimum And 0.005 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.158 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.2469 Inches Maximum
<b>Head Minor Diameter:</b>	0.185 Nominal Mils And 0.195 Nominal Centimeters
<b>Countersink Height:</b>	0.0372 Inches Nominal
<b>Shear Strength:</b>	33000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1097 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097D5-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.