

**Description**

length: 5/16" diameter: 3/16", solid rivet, flush shear head 2017-t4 aluminum alloy, roughly 990 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1097D65
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-916-9542
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



## P/N NAS1097D6-5 Specifications

<b>Fastener Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.004 Inches Minimum And 0.006 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.189 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.2749 Inches Minimum And 0.3016 Inches Maximum
<b>Head Minor Diameter:</b>	0.198 Inches Minimum And 0.208 Inches Maximum
<b>Countersink Height:</b>	0.046 Inches Nominal
<b>Shear Strength:</b>	33000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1097 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097D6-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.