

## Description

length: 3/4" diameter: 1/4", solid rivet - 100°, flush shear head - 2017-t4 aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1097D812
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-349-5209
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N NAS1097D8-12 Specifications

<b>Fastener Length:</b>	0.750 Inches Nominal
<b>Head Style:</b>	Oval Countersunk
<b>Shank Diameter:</b>	0.249 Inches Minimum And 0.252 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.249 Inches Minimum And 0.252 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Mil-r-5674 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1097 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097D8-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.