

Description

length: 3/4" diameter: 1/4", solid rivet - 100°, flush shear head - 2017-t4 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097D812
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-349-5209
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1097D8-12 Specifications

Fastener Length:	0.750 Inches Nominal
Head Style:	Oval Countersunk
Shank Diameter:	0.249 Inches Minimum And 0.252 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.249 Inches Minimum And 0.252 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Mil-r-5674 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097D8-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.