

## Description

length: 1/2" diameter: 1/4", solid rivet - 100°, flush shear head - 2017-t4 aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1097D88
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-559-6855
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N NAS1097D8-8 Specifications

<b>Fastener Length:</b>	0.500 Inches Nominal
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.004 Inches Minimum And 0.006 Inches Maximum
<b>Shank Diameter:</b>	0.249 Inches Minimum And 0.252 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.390 Inches Minimum And 0.395 Inches Maximum
<b>Head Minor Diameter:</b>	0.316 Inches Minimum And 0.326 Inches Maximum
<b>Countersink Height:</b>	0.060 Inches Nominal
<b>End Item Identification:</b>	A-10 Aircraft
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Surface Treatment:</b>	Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Class 1a Yellow Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097D8-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.