

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1097DD56 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-902-8678 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N NAS1097DD5-6 Specifications

| | |
|--|--|
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.003 Inches Nominal |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.225 Inches Minimum And 0.247 Inches Maximum |
| Head Minor Diameter: | 0.185 Nominal Mils And 0.195 Nominal Centimeters |
| Countersink Height: | 0.037 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Specification/standard Data: | 80205-nas1097 Professional/Industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097DD5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.