

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097DD56
Minimum Qty (MOQ):	100
NSN:	5320-00-902-8678
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1097DD5-6 Specifications

Fastener Length:	0.375 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Nominal
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.225 Inches Minimum And 0.247 Inches Maximum
Head Minor Diameter:	0.185 Nominal Mils And 0.195 Nominal Centimeters
Countersink Height:	0.037 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1097 Professional/Industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097DD5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.