

**Description**

Fastener Length: 7/16", NAS1097 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1097DD57
Minimum Qty (MOQ):	100
NSN:	5320-00-926-5863
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

# P/N NAS1097DD5-7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.240 Inches Minimum And 0.247 Inches Maximum
Head Minor Diameter:	0.185 Inches Minimum And 0.195 Inches Maximum
Countersink Height:	0.037 Inches Nominal
Grip Length:	0.204 Inches Nominal
Shear Strength:	37000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097DD5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.