

**Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1097DD610        |
| Minimum Qty (MOQ):      | 200 EA              |
| NSN:                    | 5320-00-464-7419    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N NAS1097DD6-10 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.615 Inches Minimum And 0.635 Inches Maximum              |
| <b>Head Style:</b>                                    | Undersized Oval Countersunk                                |
| <b>Head Height:</b>                                   | 0.004 Inches Minimum And 0.006 Inches Maximum              |
| <b>Shank Diameter:</b>                                | 0.186 Inches Minimum And 0.189 Inches Maximum              |
| <b>Shank Style:</b>                                   | Straight   |
| <b>Head Major Diameter:</b>                           | 0.275 Inches Minimum And 0.302 Inches Maximum              |
| <b>Head Minor Diameter:</b>                           | 0.198 Inches Minimum And 0.208 Inches Maximum              |
| <b>Countersink Height:</b>                            | 0.046 Inches Nominal                                       |
| <b>Shear Strength:</b>                                | 37000 Single Pounds Per Square Inch                        |
| <b>Countersink Angle:</b>                             | 99.5 Degrees Minimum And 100.5 Degrees Maximum             |
| <b>Heat Treatment:</b>                                | T-4 Solution Heat Treated Overall                          |
| <b>Material:</b>                                      | Aluminum Alloy 2024 Overall                                |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Overall         |
| <b>Surface Treatment:</b>                             | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Mil Spec Single Treatment Response Overall      |
| <b>Specification/standard Data:</b>                   | 80205-nas1097 Professional/Industrial Association Standard |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097DD6-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.