

# P/N NAS1097DD6-12

### **Description**

Fastener Length: 3/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1097DD612
Minimum Qty (MOQ):	170 EA
NSN:	5320-00-935-3692
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1097DD6-12 Specifications

Fastener Length:	0.750 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.004 Inches Nominal
Shank Diameter:	0.188 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.275 Inches Minimum And 0.302 Inches Maximum
Head Minor Diameter:	0.198 Nominal Mils And 0.208 Nominal Centimeters
Countersink Height:	0.046 Inches Nominal
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097DD6-12">https://military-fasteners.com/rivets/solid+rivets/NAS1097DD6-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.