

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1097KE310 |
| Minimum Qty (MOQ): | 115 EA |
| NSN: | 5320-01-163-6511 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N NAS1097KE3-10 Specifications

| | |
|-------------------------------------------------------|-------------------------------------------------------|
| Identification Code Color: | Violet |
| Fastener Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.003 Inches Minimum And 0.005 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.096 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.1478 Inches Maximum |
| Head Minor Diameter: | 0.086 Nominal Mils And 0.096 Nominal Centimeters |
| Countersink Height: | 0.021 Inches Nominal |
| Countersink Angle: | 99.5 Degrees Minimum And 100.0 Degrees Maximum |
| Heat Treatment: | T-81 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2219 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.