

Description

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1097KE310        |
| Minimum Qty (MOQ):      | 115 EA              |
| NSN:                    | 5320-01-163-6511    |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N NAS1097KE3-10 Specifications

|   |   |
|---|---|
| <b>Identification Code Color:</b>                     | Violet  |
| <b>Fastener Length:</b>                               | 0.615 Inches Minimum And 0.635 Inches Maximum         |
| <b>Head Style:</b>                                    | Undersized Oval Countersunk                           |
| <b>Head Height:</b>                                   | 0.003 Inches Minimum And 0.005 Inches Maximum         |
| <b>Shank Diameter:</b>                                | 0.093 Inches Minimum And 0.096 Inches Maximum         |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip                       |
| <b>Head Major Diameter:</b>                           | 0.1478 Inches Maximum                                 |
| <b>Head Minor Diameter:</b>                           | 0.086 Nominal Mils And 0.096 Nominal Centimeters      |
| <b>Countersink Height:</b>                            | 0.021 Inches Nominal                                  |
| <b>Countersink Angle:</b>                             | 99.5 Degrees Minimum And 100.0 Degrees Maximum        |
| <b>Heat Treatment:</b>                                | T-81 Solution Heat Treated Overall                    |
| <b>Material:</b>                                      | Aluminum Alloy 2219 Overall                           |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Overall    |
| <b>Surface Treatment:</b>                             | Anodize Overall                                       |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.