

Description

Fastener Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1097KE33A |
| Minimum Qty (MOQ): | 1000 EA |
| NSN: | 5320-01-528-0975 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



NO IMAGE
AVAILABLE

P/N NAS1097KE3-3A Specifications

| | |
|---|---|
| Fastener Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.003 Inches Minimum And 0.005 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.096 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.126 Inches Minimum And 0.148 Inches Maximum |
| Head Minor Diameter: | 0.086 Inches Minimum And 0.096 Inches Maximum |
| Countersink Height: | 0.021 Inches Nominal |
| End Item Identification: | F-15 Aircraft |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 7050 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Ttype li0.mil-a-8625 Ttype li0class 1 Clear Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-3A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.