

**Description**

Fastener Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097KE33A
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-528-0975
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

## P/N NAS1097KE3-3A Specifications

<b>Fastener Length:</b>	0.178 Inches Minimum And 0.198 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.003 Inches Minimum And 0.005 Inches Maximum
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.096 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.126 Inches Minimum And 0.148 Inches Maximum
<b>Head Minor Diameter:</b>	0.086 Inches Minimum And 0.096 Inches Maximum
<b>Countersink Height:</b>	0.021 Inches Nominal
<b>End Item Identification:</b>	F-15 Aircraft
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 7050 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Ttype li0.mil-a-8625 Ttype li0class 1 Clear Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-3A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.