

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097KE36
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-169-0729
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N NAS1097KE3-6 Specifications

Fastener Length:	0.375 Inches Nominal
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.096 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.1478 Inches Maximum
Head Minor Diameter:	0.086 Nominal Mils And 0.096 Nominal Centimeters
Countersink Height:	0.021 Inches Nominal
Shear Strength:	41000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Optional Square End
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.