

## **P/N NAS1097KE3-6A**

### **Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:

Minimum Qty (MOQ):

NSN:

S320-01-393-7792

National Motor Freight:

NAS1097KE36A

1000 EA

095190, Hardware, Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1097KE3-6A Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Shovel
Head Height:	0.021 Inches Nominal
Shank Diameter:	0.093 Inches Minimum And 0.096 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.086 Inches Minimum And 0.096 Inches Maximum
Countersink Height:	0.003 Inches Minimum And 0.006 Inches Maximum
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Mil-r-5674 Mil Std Single Material Response Overall
Surface Treatment:	Anodize Overall

# **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-6A">https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-6A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-6A">https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-6A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-6A">https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-6A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-6A">https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-6A</a> and selecting the quantity you want then contain the property of the property