

Description

Fastener Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097KE37A
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-393-7795
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

P/N NAS1097KE3-7A Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.021 Inches Nominal
Shank Diameter:	0.093 Inches Minimum And 0.098 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.1405 Inches Minimum And 0.1478 Inches Maximum
Head Minor Diameter:	0.1263 Nominal Inches
Countersink Height:	0.021 Inches Nominal
Countersink Angle:	70.0 Degrees Minimum And 130.0 Degrees Maximum
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Mil-r-5674 Mil Std Single Material Response Overall
Surface Treatment:	Anodize Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.