

## Description

Fastener Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1097KE37A
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-393-7795
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N NAS1097KE3-7A Specifications

<b>Fastener Length:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Head Style:</b>	Undersized Oval Countersunk
<b>Head Height:</b>	0.021 Inches Nominal
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.098 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.1405 Inches Minimum And 0.1478 Inches Maximum
<b>Head Minor Diameter:</b>	0.1263 Nominal Inches
<b>Countersink Height:</b>	0.021 Inches Nominal
<b>Countersink Angle:</b>	70.0 Degrees Minimum And 130.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 7050 Overall
<b>Material Document And Classification:</b>	Mil-r-5674 Mil Std Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.