

Description

Fastener Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1097KE39A |
| Minimum Qty (MOQ): | 500 EA |
| NSN: | 5320-01-451-5665 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N NAS1097KE3-9A Specifications

| | |
|--|---|
| Fastener Length: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.021 Inches Nominal |
| Shank Diameter: | 0.093 Inches Minimum And 0.098 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.1405 Inches Minimum And 0.1478 Inches Maximum |
| Head Minor Diameter: | 0.1263 Nominal Inches |
| Countersink Height: | 0.021 Inches Nominal |
| End Item Identification: | F-15s |
| Countersink Angle: | 70.0 Degrees Minimum And 130.0 Degrees Maximum |
| Criticality Code Justification: | Agav |
| Material: | Aluminum Alloy 7050 Overall |
| Material Document And Classification: | Mil-r-5674 Mil Std Single Material Response Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE3-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.