

Description

length: 1/4" diameter: 5/32", solid rivet, flush shear head, 7050-t73 aluminum alloy, roughly 1730 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097KE54
Minimum Qty (MOQ):	100
NSN:	5320-01-025-1809
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N NAS1097KE5-4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.2251 Inches Minimum And 0.2469 Inches Maximum
Head Minor Diameter:	0.185 Inches Minimum And 0.195 Inches Maximum
Countersink Height:	0.0372 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	T-81 Solution Heat Treated Overall
Material:	Aluminum Alloy 2219 Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/Industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.