

Description

length: 7/16" diameter: 5/32", flush shear head, aluminum alloy, roughly 1090 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097KE57
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-024-3403
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N NAS1097KE5-7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.003 Inches Minimum And 0.005 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.158 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.225 Inches Minimum And 0.247 Inches Maximum
Head Minor Diameter:	0.185 Inches Minimum And 0.195 Inches Maximum
Countersink Height:	0.037 Inches Nominal
Shear Strength:	715 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy 7050 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1097 Professional/Industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.