

Description

Fastener Length: 1-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1097KE832A |
| Minimum Qty (MOQ): | 505 EA |
| NSN: | 5320-01-045-2500 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N NAS1097KE8-32A Specifications

| | |
|---|---|
| Fastener Length: | 1.990 Inches Minimum And 2.010 Inches Maximum |
| Head Style: | Undersized Oval Countersunk |
| Head Height: | 0.004 Inches Minimum And 0.006 Inches Maximum |
| Shank Diameter: | 0.249 Inches Minimum And 0.252 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.3710 Inches Minimum And 0.3948 Inches Maximum |
| Head Minor Diameter: | 0.316 Inches Minimum And 0.326 Inches Maximum |
| Countersink Height: | 0.060 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Heat Treatment: | T-81 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2219 Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE8-32A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.