

Description

Fastener Length: 1-63/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097KE832A
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-045-2500
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N NAS1097KE8-32A Specifications

Fastener Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Head Style:	Undersized Oval Countersunk
Head Height:	0.004 Inches Minimum And 0.006 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.252 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.3710 Inches Minimum And 0.3948 Inches Maximum
Head Minor Diameter:	0.316 Inches Minimum And 0.326 Inches Maximum
Countersink Height:	0.060 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	T-81 Solution Heat Treated Overall
Material:	Aluminum Alloy 2219 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097KE8-32A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.