

**Description**

Fastener Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1097U575
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-030-8455
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1097U5-7-5 Specifications

<b>Fastener Length:</b>	0.459 Inches Minimum And 0.479 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.160 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.225 Inches Minimum And 0.247 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Mms1220 Columbium Alloy Fscm 76301 Mfr Ref Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097U5-7-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.