

Description

Fastener Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1097U575
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-030-8455
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N NAS1097U5-7-5 Specifications

Fastener Length:	0.459 Inches Minimum And 0.479 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.225 Inches Minimum And 0.247 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	Annealed Overall
Material:	Titanium Alloy Overall
Material Document And Classification:	Mms1220 Columbium Alloy Fscm 76301 Mfr Ref Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097U5-7-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.