

Description

Fastener Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS1097U67 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-01-045-3004 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1097U6-7 Specifications

| | |
|--|--|
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.186 Inches Minimum And 0.191 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.2749 Inches Minimum And 0.3030 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams4982 Columbium Alloy Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1097U6-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.