



★ FASTENERS

Military-Fasteners.com

P/N NAS1100-06-38

Description


Fastener Length: 2-11/32", Thread: 6-32, Thread Length: 1-3/4", pan head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS11000638
Minimum Qty (MOQ):	5
NSN:	5305-01-070-1099
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1100-06-38 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	2.262 Inches Minimum And 2.356 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1100 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1100-06-38> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.