



★ FASTENERS

Military-Fasteners.com

P/N NAS1100-08-14

Description


Fastener Length: 7/8", Thread: 8-32, Thread Length: 7/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS11000814
Minimum Qty (MOQ):	50
NSN:	5305-00-815-6119
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1100-08-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.813 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.875 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6059 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams @6300 Assn Std 6th Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1100-08-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.