

P/N NAS1100-08-20

Military-Fasteners.com

Description

Fastener Length: 1-1/4", Thread: 8-32, Thread Length: 1-1/4

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS11000820
Minimum Qty (MOQ):	25
NSN:	5305-00-060-4351
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1100-08-20 Specifications

Thread Class:3aThread Direction:Right-handRight-handRight-handThread Length:1.188 Inches Minimu And 1.250 Inches MaximumFastener Length:1.250 Inches NominalHead Style:PanHead Diameter:0.306 Inches Minimu And 0.322 Inches MaximumHead Height:0.105 Inches Minimu And 0.115 Inches MaximumInternal Drive Style:Torque SetNominal Thread Dlameter:0.164 Inches10600 Pounds Per Square Inch32Screw Material Document And6.0 Rockwell C MaximumScrew Material Document And6.0 Rockwell C Comp 8740 Or Steel Comp 8750 Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Surface Treatment:Cadmium And ChromateScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment:On-putafic Space Single Treatment ResponseScrew Surface Treatment:On-putafic Space Single Treatment ResponseScrew Surface Treatment:No-putafic Space Sin		
Thread Length:1.188 Inches Minimum And 1.250 Inches MaximumFastener Length:1.250 Inches NominalHead Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumInternal Drive Style:Torque SetNominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:160000 Pounds Per Square InchBarcew Material:Seel Comp Eq340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4100 r Steel Comp 4037Screw Material:Keile Comp Eq340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4100 r Steel Comp 4037Screw Material:Keile Comp Eq340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4037Screw Material:Keile Comp Eq340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4037Screw Surface Treatment:Cadmium And ChromateScrew Surface Treatment:Cadmium And Spec Single Treatment ResponseSocument And Classification:Q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Thread Class:	За
Fastener Length:1.250 Inches NominalHead Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumInternal Drive Style:Torque SetNominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:6.0.0 Rockwell C Minimum And 4.0.0 Rockwell C MaximumScrew Material Document AndWils-Sto00 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment:Cadmium And Chromate<	Thread Direction:	Right-hand
Head Style:PanHead Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumInternal Drive Style:Torque SetNominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew MaterialSteel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6300 Assn Std 6th Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Thread Length:	1.188 Inches Minimum And 1.250 Inches Maximum
Head Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumInternal Drive Style:Torque SetNominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6028 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-6026 Mil Spec 5th Material Response Or Ams 6300 Assn 5td 6th Material Response Or Mil-s-803 Mil Spec 4th Material Response Or Mil-s-6026 Mil Spec 5th Material Response Or Ams 6300 Assn 5td 6th Material Response Or Mil-s-803 Mil Spec 4th Material Response Or Mil-s-6026 Mil Spec 5th Material Response Or Ams 6300 Assn 5td 6th Material Response Or Mil-s-803 Mil Spec 4th Material Response Or Mil-s-6026 Mil Spec 5th Material Response Or Ams 6300 Assn 5td 6th Material Response Or Mil-s-803 Mil Spec 4th Material Response Or Mil-s-6026 Mil Spec 5th Material Response Or Ams 6300 Assn 5td 6th Material Response Or Ams 6300 Assn 5td 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment:Oq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Fastener Length:	1.250 Inches Nominal
Head Height:0.105 Inches Minimum And 0.115 Inches MaximumInternal Drive Style:Torque SetNominal Thread Diameter:0.164 Inches0.164 Inches32Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6300 Assn Std 6th Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment:Q-p-416 Ty 2 CI 3 Fed Spec Single Treatment Response	Head Style:	Pan
Internal Drive Style:Torque SetNominal Thread Diameter:0.164 InchesDiameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment:Q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Nominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Amil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateOcument And Classification:Qe-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface TreatmentQq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Internal Drive Style:	Torque Set
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Nominal Thread Diameter:	0.164 Inches
Hardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Thread Quantity Per Inch:	32
Screw Material:Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface TreatmentQq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface TreatmentQq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Classification:Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface TreatmentQq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Screw Material:	Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037
Screw Surface Treatment Document And Classification:		
Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response	Screw Surface Treatment:	Cadmium And Chromate
Thread Series Designator: Unc		Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
	Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1100-08-20</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.