

Description

Fastener Length: 1-1/2", Thread: 1/4-28, Thread Length: 1-1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1100424 |
| Minimum Qty (MOQ): | 40 EA |
| NSN: | 5305-00-913-7888 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1100-4-24 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.429 Inches Minimum And 1.500 Inches Maximum |
| Fastener Length: | 1.500 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.473 Inches Minimum And 0.492 Inches Maximum |
| Head Height: | 0.162 Inches Minimum And 0.175 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Screw Material: | Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037 |
| Screw Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1100-4-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.