

Description

Fastener Length: 5/8", Thread: 2-56, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1100E0210
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-010-4362
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1100E02-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.558 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.063 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1100 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1100E02-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.