

**Description**

Fastener Length: 1/2", Thread: 6-32, Thread Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1100E068
Minimum Qty (MOQ):	10
NSN:	5305-00-020-3639
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1100E06-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.407 Inches Minimum And 0.500 Inches Maximum
<b>Fastener Length:</b>	0.469 Inches Minimum And 0.500 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.256 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.087 Inches Minimum And 0.097 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1100 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1100E06-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.