



Military-Fasteners.com

P/N NAS1100E4-30

Description

Fastener Length: 1-63/64", Thread: 1/4-28, Thread Length: 1-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1100E430
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-114-1264
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1100E4-30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.867 Inches Minimum And 2.000 Inches Maximum
Fastener Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.367 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.133 Inches Minimum And 0.150 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1101 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1100E4-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.