

P/N NAS1100E4-8

Description

Screw part number

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1100E48

Minimum Qty (MOQ): 20 EA

NSN: 5305-01-010-9916

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N NAS1100E4-8 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.398 Inches Minimum And 0.500 Inches Maximum |
| Fastener Length: | 0.469 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.473 Inches Minimum And 0.492 Inches Maximum |
| Head Height: | 0.162 Inches Minimum And 0.175 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| lii Part Name Assigned By Controlling Agency: | Navy Special Project |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1100 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1100E4-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1100E4-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1100E4-8 and selecting the quantity you want then click "add to cart".