

P/N NAS1100V3-5

Description

Fastener Length: 5/16", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1100V35
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-047-0348
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



^{*} See page 2 for technical characteristics

P/N NAS1100V3-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.219 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Titanium Alloy
Screw Material Document And Classification:	Nas621 Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-1100 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1100V3-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1100V3-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1100V3-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS1100V3-5 and selecting the quantity you want then