

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS1100V37 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5305-00-004-5178 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



P/N NAS1100V3-7 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.345 Inches Minimum And 0.438 Inches Maximum |
| Fastener Length: | 0.407 Inches Minimum And 0.438 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Titanium Alloy |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1100 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1100V3-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.