

**Description**

Fastener Length: 5/8", Thread: 4-40, Thread Length: 5/8",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS11010410
Minimum Qty (MOQ):	10
NSN:	5305-00-482-9697
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1101-04-10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.544 Inches Minimum And 0.625 Inches Maximum
<b>Fastener Length:</b>	0.594 Inches Minimum And 0.625 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.178 Inches Minimum And 0.183 Inches Maximum
<b>Head Height:</b>	0.059 Inches Minimum And 0.069 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740
<b>Screw Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1101 Professional/Industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101-04-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.