

P/N NAS1101-04-14

Description

Fastener Length: 7/8", Thread: 4-40, Thread Length: 7/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS11010414


Minimum Qty (MOQ): 25

NSN: 5305-01-595-4665

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel









^{*} See page 2 for technical characteristics

P/N NAS1101-04-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.794 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Flat Fillister
Head Diameter:	0.178 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Part Name Assigned By Controlling Agency:	Screw, Machine-flat Fillister Head, Full Thread, Offset Cruciform
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Std Single Material Response Or Ams 6415 National Spec Single Material Response Or Mil-s-6049 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416, Typ Ii, Cl 2 Assn Std Single Treatment Response
Thread Series Designator:	Unjc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1101-04-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.