

# P/N NAS1101-04-8

Military-Fasteners.com

#### Description

Fastener Length: 1/2", Thread: 4-40, Thread Length: 15/32", NAS1101 series screw

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS1101048                                |
|-------------------------|---|
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5305-00-917-6057                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1101-04-8 Specifications

| Thread Class:   | За  |
|---|---|
| Thread Direction:                                       | Right-hand  |
| Thread Length:  | 0.419 Inches Minimum And 0.469 Inches Maximum   |
| Fastener Length:  | 0.469 Inches Minimum And 0.500 Inches Maximum   |
| Head Style:   | Flat Chamfer  |
| Head Diameter:  | 0.178 Inches Minimum And 0.183 Inches Maximum   |
| Head Height:  | 0.059 Inches Minimum And 0.069 Inches Maximum   |
| Internal Drive Style:                                   | Torque Set  |
| Nominal Thread Diameter:                                | 0.112 Inches  |
| Thread Quantity Per Inch:                               | 40  |
| Minimum Tensile Strength:                               | 160000 Pounds Per Square Inch   |
| Hardness Rating:  | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum   |
| Screw Material:   | Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740  |
| Screw Material Document And<br>Classification:          | Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response |
| Screw Surface Treatment:                                | Cadmium And Chromate  |
| Screw Surface Treatment Document<br>And Classification: | Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses  |
| Thread Series Designator:                               | Unc   |
| Specification/standard Data:                            | 80205-nas1101 Professional/industrial Association Standard  |

### How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1101-04-8</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.