

**Description**

Fastener Length: 3/8", Hole Diameter: 1/32", Thread: 4-40, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS110104H6                               |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-130-8170                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1101-04H6 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.294 Inches Minimum And 0.375 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 0.344 Inches Minimum And 0.375 Inches Maximum  |
| <b>Head Style:</b>  | Flat Chamfer   |
| <b>Head Diameter:</b>                                       | 0.178 Inches Minimum And 0.183 Inches Maximum  |
| <b>Head Height:</b>   | 0.059 Inches Minimum And 0.069 Inches Maximum  |
| <b>Hole Diameter:</b>                                       | 0.034 Inches Minimum And 0.042 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Torque Set   |
| <b>Nominal Thread Diameter:</b>                             | 0.112 Inches   |
| <b>Hole Quantity:</b>                                       | 1  |
| <b>Thread Quantity Per Inch:</b>                            | 40   |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                                     | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum  |
| <b>Screw Material:</b>                                      | Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response  |
| <b>Head Hole Configuration Style:</b>                       | Round  |
| <b>Thread Series Designator:</b>                            | Unjc   |
| <b>Specification/standard Data:</b>                         | 80205-nas1101 Professional/industrial Association Standard                                   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101-04H6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.