

Description

Fastener Length: 1-7/8", Thread: 6-32, Thread Length: 1-7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS11010630
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-059-0181
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1101-06-30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.751 Inches Minimum And 1.875 Inches Maximum
Fastener Length:	1.813 Inches Minimum And 1.875 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.221 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.074 Inches Minimum And 0.086 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1101 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101-06-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.