

P/N NAS1101-06H4

Military-Fasteners.com

Description

Hole Diameter: 1/32", Thread Length: 1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS110106H4
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-165-1874
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS1101-06H4 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.157 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.221 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.074 Inches Minimum And 0.086 Inches Maximum
Hole Diameter:	0.038 Inches Nominal
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	2
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
lii Part Name Assigned By Controlling Agency:	Navy Special Project
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Head Hole Configuration Style:	Round
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1101 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1101-06H4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.