

# P/N NAS1101-08-16

## **Description**

Fastener Length: 63/64", Thread: 8-32, Thread Length: 63/64",

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS11010816

Minimum Qty (MOQ): 25

NSN: 5305-00-920-9967

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1101-08-16 Specifications

| Thread Class:                                        | 3a                                                                                                                                                                                                                            |
|------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Thread Direction:                                    | Right-hand                                                                                                                                                                                                                    |
| Thread Length:                                       | 0.907 Inches Minimum And 1.000 Inches Maximum                                                                                                                                                                                 |
| Fastener Length:                                     | 0.969 Inches Minimum And 1.000 Inches Maximum                                                                                                                                                                                 |
| Head Style:                                          | Flat Chamfer                                                                                                                                                                                                                  |
| Head Diameter:                                       | 0.265 Inches Minimum And 0.270 Inches Maximum                                                                                                                                                                                 |
| Head Height:                                         | 0.088 Inches Minimum And 0.102 Inches Maximum                                                                                                                                                                                 |
| Internal Drive Style:                                | Torque Set                                                                                                                                                                                                                    |
| Nominal Thread Diameter:                             | 0.164 Inches                                                                                                                                                                                                                  |
| Thread Quantity Per Inch:                            | 32                                                                                                                                                                                                                            |
| Minimum Tensile Strength:                            | 160000 Pounds Per Square Inch                                                                                                                                                                                                 |
| Hardness Rating:                                     | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum                                                                                                                                                                           |
| Screw Material:                                      | Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740                                                                                                                                  |
| Screw Material Document And Classification:          | Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response |
| Screw Surface Treatment:                             | Cadmium And Chromate                                                                                                                                                                                                          |
| Screw Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses                                                                                                                                                                      |
| Thread Series Designator:                            | Unjc                                                                                                                                                                                                                          |
| Specification/standard Data:                         | 80205-nas1101 Professional/industrial Association Standard                                                                                                                                                                    |

### **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1101-08-16">https://military-fasteners.com/screws/machine+screws/NAS1101-08-16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NAS1101-08-16">https://military-fasteners.com/screws/machine+screws/NAS1101-08-16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NAS1101-08-16">https://military-fasteners.com/screws/machine+screws/NAS1101-08-16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/nas101-08-16">https://military-fasteners.com/screws/nas101-08-16</a> and selecting the quantity of the property o