

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1101315
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-532-5632
Schedule B:	7318.15.6080
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1101-3-15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.906 Inches Minimum And 0.938 Inches Maximum
Fastener Length:	0.906 Inches Minimum And 0.938 Inches Maximum
Head Style:	Flat Fillister
Head Diameter:	0.306 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.103 Inches Minimum And 0.118 Inches Maximum
Internal Drive Style:	Torque Set
End Item Identification:	Rq-4a Global Hawk
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Machine
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses
Special Features:	Alloy Steel Material: 4140,4340,8740
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101-3-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.