

**Description**

Fastener Length: 15/16", Thread: 10-32, Thread Length: 15/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1101315
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-532-5632
Schedule B:	7318.15.6080
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS1101-3-15 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.906 Inches Minimum And 0.938 Inches Maximum
<b>Fastener Length:</b>	0.906 Inches Minimum And 0.938 Inches Maximum
<b>Head Style:</b>	Flat Fillister
<b>Head Diameter:</b>	0.306 Inches Minimum And 0.313 Inches Maximum
<b>Head Height:</b>	0.103 Inches Minimum And 0.118 Inches Maximum
<b>Internal Drive Style:</b>	Torque Set
<b>End Item Identification:</b>	Rq-4a Global Hawk
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Screw, Machine
<b>Screw Material:</b>	Steel
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses
<b>Special Features:</b>	Alloy Steel Material: 4140,4340,8740
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1101-3-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.